# **Product datasheet**

Specifications





### Acti9 - fuse-disconnector STI - 3 poles + N - 25 A - for fuse 10.3 x 38 mm

Local distributor code: 401403235

A9N15658

EAN Code: 3606480619595

#### Main

| Range                     | Acti9             |
|---------------------------|-------------------|
| Product name              | Acti9 STI         |
| Product or component type | Fuse-disconnector |
| Device short name         | STI               |
| poles description         | 3P + N            |

### Complementary

| Complementary                  |   |
|--------------------------------|---|
| [In] rated current             | 2 A   |
|                                | 4 A   |
|                                | 6 A   |
|                                | 10 A  |
|                                | 16 A  |
|                                | 20 A  |
|                                | 25 A  |
| Fuse curve                     | AM  |
|                                | GG  |
| Fuse size                      | 10.3 x 38 mm  |
| [Ue] rated operational voltage | 500 V AC  |
| [Ui] rated insulation voltage  | 500 V AC 50/60 Hz   |
| mounting mode                  | Clip-on   |
| mounting support               | DIN rail  |
| 9 mm pitches                   | 6   |
| Height                         | 81 mm   |
| Width                          | 54 mm   |
| Depth                          | 75 mm   |
| Colour                         | White   |
| Connections - terminals        | Screw clamp terminals1 cable(s) 0.7510 mm² rigid              |
|                                | Screw clamp terminals1 cable(s) 0.56 mm <sup>2</sup> flexible |
|                                | Screw clamp terminals2 cable(s) 0.754 mm² rigid               |
|                                | Screw clamp terminals2 cable(s) 0.56 mm² flexible             |
| Wire stripping length          | 12 mm   |
| Tightening torque              | 2 N.m   |

### Environment

| Standards               | IEC 60269-1/2<br>IEC EN 60947-3 |
|-------------------------|---------------------------------|
| IP degree of protection | IP20                            |

| Pollution degree                      | 3        |
|---------------------------------------|----------|
| Ambient air temperature for operation | -2060 °C |
| Ambient air temperature for storage   | -4080 °C |

# **Packing Units**

| J                            |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 7.500 cm  |
| Package 1 Width              | 5.400 cm  |
| Package 1 Length             | 8.600 cm  |
| Package 1 Weight             | 182.000 g |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 4         |
| Package 2 Height             | 3.900 cm  |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 20.000 cm |
| Package 2 Weight             | 785.000 g |
| Unit Type of Package 3       | S03       |
| Number of Units in Package 3 | 48        |
| Package 3 Height             | 30.000 cm |
| Package 3 Width              | 30.000 cm |
| Package 3 Length             | 40.000 cm |
| Package 3 Weight             | 9.775 kg  |
|                              |           |

## **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration  |
| China Rohs Regulation    | China RoHS declaration<br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                 |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |