




---

 PRODUCT-DETAILS

## F202 A S-100/0.1

### F202 A S-100/0.1 Residual Current Circuit Breaker 2P Type A 100 mA




---

**General Information**

Extended Product Type	F202 A S-100/0.1
Product ID	2CSF202201R2900
EAN	8012542916000
Catalog Description	F202 A S-100/0.1 Residual Current Circuit Breaker 2P Type A 100 mA
Long Description	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.

---

**ABB EcoSolutions**

ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108469A3794

---

**Circular Value**

Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 52.5 %
---	---

Group Waste to Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging	Recycled Paper - 78 %
Offered with Extended Lifetime	Product Durability
End of Life Instructions	9AKK108468A4361

### Eco Transparency

Environmental Product Declaration - EPD	9AKK108467A3700
---	-----------------

### Technical

Standards	IEC/EN 61008 UL 1053
Type of Residual Current	Type A
Rated Voltage (U <sub>r</sub> )	230 V
Rated Operational Voltage	230 V
Rated Insulation Voltage (U <sub>i</sub> )	500 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Input Voltage Type	AC
Rated Current (I <sub>n</sub> )	100 A
Rated Residual Current	100 mA
Rated Conditional Short-Circuit Current (I <sub>nc</sub> )	10 kA
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	1 kA
Maximum Surge Current	5 kA
Leakage Current Type	A
Rated Frequency (f)	50 ... 60 Hz
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Number of Poles	2
Operating Characteristic	Selective
Mounting Type	DIN-Rail
Options Provided	None
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm <sup>2</sup> Rigid 35 ... 35 mm <sup>2</sup> Flexible 35 ... 35 mm <sup>2</sup>
Rated Cross-Section	4 - Multi-Wired 0...35 mm <sup>2</sup> 1 - Solid-Core 35...35 mm <sup>2</sup>

### Material Compliance

RoHS Information	9AKK106713A5602
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

RoHS Date	20211115
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	18f132b0-8f03-4611-9c59-dba03cc369bf Italy (IT)

## Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25...55 °C
Degree of Protection	IP2X
Pollution Degree	2
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	Refer to RoHS

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	277 V AC
Short-Circuit Current Rating (SCCR)	100 mA

## Dimensions

Width in Number of Modular Spacings	2
Product Net Width	0.035 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.200 kg
Built-In Depth (t <sub>2</sub> )	69 mm

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	80 mm
Package Level 1 Height	41 mm
Package Level 1 Depth / Length	94 mm
Package Level 1 Gross Weight	0.235 kg
Package Level 1 EAN	8012542916000
Package Level 2 Units	box 6 piece
Package Level 2 EAN	8012542916017

---

## Ordering

---

Minimum Order Quantity	1 piece
------------------------	---------

---



---

## Certificates and Declarations

---

Declaration of Conformity - CE	9AKK106713A5602
--------------------------------	-----------------

---



---

## Installation

---

Instructions and Manuals	9AKK107991A6127
--------------------------	-----------------

---



---

## Popular Downloads

---

Data Sheet, Technical Information	9AKK107991A8329
-----------------------------------	-----------------

---



---

## Classifications

---

ETIM 8	EC000003 - Residual current circuit breaker (RCCB)	
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	
CN8	85363030	
UNSPSC	39121601	
eClass	V11.0 : 27142201	
IDEA Granular Category Code (IGCC)	4875 >> Residual current circuit breaker (RCCB)	
Object Classification Code		F

---



---

## Accessories

---

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	2	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	2	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage Release	S2C-UA 230 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage Release	S2C-OVP1	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage Release	S2C-OVP2	1	piece
2CSF201998R0034	F3C-AR24 Autoreclosing unit	F3C-AR24	1	piece
2CSF202998R0034	F3C-AR230 Autoreclosing unit	F3C-AR230	1	piece
2CSS201998R0033	S3C-MOD24 Motor Operating Device	S3C-MOD24	1	piece
2CSS202998R0033	S3C-MOD230 Motor Operating Device	S3C-MOD230	1	piece

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs



ABB  
**Eco**  
 Solutions™