



 PRODUCT-DETAILS

S201-C4

Miniature Circuit Breaker - 1P - C - 4 A



General Information

Extended Product Type	S201-C4
Product ID	2CDS251001R0044
EAN	4016779523349
Catalog Description	Miniature Circuit Breaker - 1P - C - 4 A

Long Description	<p>System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.</p>
------------------	---

ABB EcoSolutions

ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108469A3796
Circular Design	Design for Closing Resource Loops - Standard EN45555 - 87.8 %
Principles Recyclability	

Rate	
Offered with Extended Lifetime	Product Durability
End of Life Instructions	9AKK108468A3132
Environmental Product Declaration - EPD	9AKK108467A7832

Technical

Standards	IEC/EN 60898-1 IEC/EN 60947-2 UL 1077
Tripping Characteristic	C
Rated Operational Voltage	acc. to IEC 60898-1 230 / 400 V AC acc. to IEC 60898-1 230 V acc. to IEC 60947-2 230 V AC
Operational Voltage	Maximum (Incl. Tolerance) 253 V AC Maximum (Incl. Tolerance) 72 V DC Minimum 12 V AC Minimum 12 V DC
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Dielectric Test Voltage	50/60 Hz-1 min: 2 kV
Input Voltage Type	AC/DC
Rated Current (I _n)	4 A
Rated Short-Circuit Capacity	(AC) 6 kA (DC) 6 kA (230 / 400 V AC) 6 kA (230 V) 6 kA (400 V) 6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(133 V AC) 20 kA (230 V AC) 10 kA (24 V DC) 20 kA (60 V DC) 10 kA (230 V) 10 kA (400 V) 10 kA
Rated Conditional Short-Circuit Current (I _{nc})	(230 V) 10 kA (400 V) 10 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(133 V AC) 15 kA (230 V AC) 7.5 kA
Frequency (f)	50 Hz
Rated Frequency (f)	50 / 60 Hz
Power Loss	1.8 W at Rated Operating Conditions per Pole 1.8 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	20000 AC cycle
Mechanical Endurance	20000 cycle
Number of Poles	1
Number of Protected Poles	1
Overvoltage Category	III
Tightening Torque	2.8 N·m

Mounting Type	DIN-Rail
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking	I / O
Actuator Material	Insulation Group II, Black, Sealable
Housing Material	Insulation Group II, RAL 7035
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Connecting Capacity	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
Installation Size	acc. to DIN 43880 1
Wire Stripping Length	12.5 mm
Terminal Type	Screw Terminals

Material Compliance

RoHS Information	2CDK403001D0607
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0335
REACH Declaration	9AKK107492A1906
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	e6800e55-46b1-49a3-881b-0f66d0e903ad Germany (DE)

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Reference Ambient Air Temperature	30 °C
Degree of Protection	IP20 IP40 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms

Technical UL/CSA

Maximum Operating Voltage UL/CSA	60 V DC 480Y/277 V AC
Interrupting Rating acc. to UL1077	(277 V AC) 6 kA (60 V DC) 10 kA

	(120 V) 10 kA
Connecting Capacity UL/CSA	Busbar 18-8 AWG Conductor 18-4 AWG
Tightening Torque UL/CSA	18 in-lb

Dimensions

Width in Number of Modular Spacings	1.0
Product Net Width	17.5 mm
Product Net Height	88 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.125 kg
Pole Net Weight	0.125 kg
Built-In Depth (t ₂)	69 mm
Dimension Diagram	2CDC022007F0010

Container Information

Package Level 1 Units	carton 10 piece
Package Level 1 Width	92 mm
Package Level 1 Height	80 mm
Package Level 1 Depth / Length	183 mm
Package Level 1 Gross Weight	1.295 kg
Package Level 1 EAN	4016779606738
Package Level 2 Units	carton 120 piece
Package Level 2 Width	275 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	14.8 kg
Package Level 2 EAN	4016779970563

Ordering

Minimum Order Quantity	1 piece
E-Number (Finland)	3211007
E-Number (Norway)	1664843
E-Number (Sweden)	2100506

Certificates and Declarations

Certification Agency	EN IEC UL
Declaration of Conformity - CE	2CDK403001D0607
Declaration of Conformity - UKCA	9AKK108467A5053
I ² t Characteristic	9AKK107992A5102

Installation	
Instructions and Manuals	2CDS207104P0002

Popular Downloads	
Data Sheet, Technical Information	9AKK107991A8329
I ² t Characteristic	9AKK107992A5102

Classifications	
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 27141901
IDEA Granular Category Code (IGCC)	4897 >> Miniature circuit breakers
Object Classification Code	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200912R0001	Auxiliary Contact	S2C-H6R	1	piece
2CDS200970R0031	Auxiliary Contact	S2C-H01	1	piece
2CDS200970R0032	Auxiliary Contact	S2C-H10	1	piece
2CDS200936R0001	Auxiliary Contact	S2C-H11L	1	piece
2CDS200936R0002	Auxiliary Contact	S2C-H20L	1	piece
2CDS200936R0003	Auxiliary Contact	S2C-H02L	1	piece
2CDS200946R0001	Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200909R0001	Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	Shunt Trip	S2C-A2	1	piece
2CSS200911R0001	Undervoltage Release	S2C-UA 12 DC	1	piece
2CSS200911R0002	Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0003	Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200911R0004	Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0005	Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200911R0007	Undervoltage Release	S2C-UA 24 DC	1	piece
2CSS200911R0008	Undervoltage Release	S2C-UA 48 DC	1	piece
2CSS200911R0009	Undervoltage Release	S2C-UA 110 DC	1	piece
2CSS200911R0010	Undervoltage Release	S2C-UA 230 DC	1	piece
GHS2001901R0003	Mechanical Accessories	S2C-DH	1	piece
2CSS200998R0001	Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	Plug-in base	S2C-EST	1	piece
2CDS200918R0001	Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	Sensor	CMS-100PS	1	piece
2CCA880101R0001	Sensor	CMS-101PS	1	piece
2CCA880102R0001	Sensor	CMS-102PS	1	piece

Where Used (as a spare part for "Products")

Identifier	Description	Quantity	Unit Of Measure
3HAC020536-014	No Description Available	1	piece

Product specific part data

Product	Robotics Part Category	Robot Design Year
3HAC020536-014	Drive Module	IRC5 M2004

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

Medium Voltage Products and Systems → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB)

Robotics → Controllers → IRC5 → IRC5 Single



360

