

Eaton 25LET

Catalog Number: 25LET

Eaton Bussmann series high speed British standard fuse, 25A, 280 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	25LET
	EAN
	5027590470896
UPC	Product Length/Depth
051712833233	55 mm
Product Height	Product Width
18 mm	18 mm
Product Weight	Compliances
32 g	CE Marked
	RoHS Compliant

Certifications

IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4

Product specifications

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

25 A

Breaking capacity

200 kA

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Rated switching capacity

200 kA

Rated voltage AC

280 V

Rated voltage DC

150 V

Center-to-center distance of connections

41 mm

Mounting dimension

M6

Current type

AC/DC

Class

Class aR

Clearing (I²T)

250

Watt losses

4 W

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogues

[IEC high speed fuse links](#)

Declarations of conformity

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Technical data sheets

[720004 LCT, LET, LMMT, LMT](#)

Fuse shape

Offset bolted tags

Pre arc (I2T)

18

Color

None

Interrupt rating

200 kA RMS Sym, 50 kA DC at 150 Vdc

Connection

Blade end x blade end

Construction size

Other

Mounting method

Stud

Packaging type

Standard

Voltage rating

280 V

Fuse type

LET

Suitable for

TI500 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Fuse system (according to IEC 60269)

Other