



PRODUCT-DETAILS

SPL20/25M

20MM GS-PVC COAT CONDUIT 25M - BL



General Information	
Extended Product Type	SPL20/25M
Product ID	7TCA296030R0140
EAN	5020963000126
Catalog Description	20MM GS-PVC COAT CONDUIT 25M - BL
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 1/2 Inch, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters. PVC Covering with Galvanised Steel Core. Black
Ordering	
EAN	5020963000126
UPC	786210246888
Country of Origin	United Kingdom (GB)
Selling Unit of Measure	each
Dimensions	
Product Net Depth / Length	25 m

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	16 in 406 mm
Package Level 1 Height	8 in 203 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 2 Units	25 piece
Package Level 2 Width	39.37 in 1000 mm
Package Level 2 Height	46.46 in 1180 mm
Package Level 2 Depth / Length	47.24 in 1200 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Effective Date	20110412
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/2 in NC20
Outside Diameter	21.1 mm
Product Name	FLEXIBLE METALLIC CONDUIT
Product Type	Oil Resistant Conduit
Radius	80 mm
RoHS Date	9AKK107992A8994

Certificates and Declarations

Data Sheet, Technical Information	SPL20/25M
Declaration of Conformity - CE	9AKK107492A9618

External Classifications and Standards

ETIM 7	EC001179 - Protective metallic hose
ETIM 8	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

