



PRODUCT-DETAILS

SPL32/25M
32MM GS-PVC COAT CONDUIT 25M - BL



General Information	
Extended Product Type	SPL32/25M
Product ID	7TCA296030R0238
EAN	5020963000577
Catalog Description	32MM GS-PVC COAT CONDUIT 25M - BL
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 1 Inch, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters. PVC Covering with Galvanised Steel Core. Black
Ordering	
EAN	5020963000577
UPC	786210247182
Country of Origin	United Kingdom (GB)
Selling Unit of Measure	each
Dimensions	
Product Net Depth / Length	25 m

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	26.77 in 680 mm
Package Level 1 Height	10.62 in 270 mm
Package Level 1 Depth / Length	26.77 in 680 mm
Package Level 2 Units	8 piece
Package Level 2 Width	39.37 in 1000 mm
Package Level 2 Height	46.46 in 1180 mm
Package Level 2 Depth / Length	47.24 in 1200 mm

Environmental

REACH Information	False - does not contain substances > 0.1 mass percentage
-------------------	---

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Effective Date	20110412
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1 in NC32
Outside Diameter	33.1 mm
Product Name	FLEXIBLE METALLIC CONDUIT
Product Type	Oil Resistant Conduit
Radius	145 mm
RoHS Date	9AKK107992A8994

Certificates and Declarations

Data Sheet, Technical Information	SPL32/25M
Declaration of Conformity - CE	9AKK107492A9618

External Classifications and Standards

ETIM 7	EC001179 - Protective metallic hose
ETIM 8	EC001179 - Protective metallic hose
ETIM 9	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

