

Panel mounted socket
Part no. 1492



- screw terminals
- suitable for through wiring
- 20° inclination
- sockets optional fitted with auxiliary contact

Technical specifications

Ampere	32 A
Poles	3 p
Voltage	230 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	standard
Protection type	IP 44
Flange	100x92 mm
Fixing hole	85x77 mm
Inclination	20 °
Weight	236 g
Declaration of Conformity	DE,VDE, NL,Kema, AT,ÖVE, CN,CQC

Drawing



Drawing 1 MB 260 Dim. in mm	Amp. Poles	16			32		
		3	4	5	3	4	5
a	73.5	100	100	100	100	100	100
b	64	92	92	92	92	92	92
c	50	59	58	62	62	61	61
d	60	85	85	85	85	85	85
e	52	77	77	77	77	77	77
f	5.5	5.5	5.5	5.5	5.5	5.5	5.5
g	7	8	8	8	8	8	8
g-1	2	2	2	2	2	2	2
h	79	100	100	103	103	106	106
k	44	34	34	54	54	49	49
l	52	55	65	67	67	72	72
l1	60	63	72	82	82	85	85
α	20°	20°	20°	20°	20°	20°	20°
Terminal for cond. cross section (mm²) min.-max.		1.5 1.5 1.5	2.5 2.5 2.5	2.5 2.5 2.5			
		-4 -4 -4	-10 -10 -10	-10 -10 -10			