


**Panel mounted socket**  
Part no. 603




- screw terminals straight

**Technical specifications**

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 2 p             |
| Voltage               | 20-25 V         |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |
| Flange                | 55x55 mm        |
| Fixing hole           | 45x45 mm        |
| Weight                | 103 g           |

**Drawing**



| Drawing<br>1 MB 136<br>Dim. in mm                   | Amp.<br>Poles | 16  |         | 32  |         |
|-----------------------------------------------------|---------------|-----|---------|-----|---------|
|                                                     |               | 2   | 3       | 2   | 3       |
| a                                                   |               | 55  | 55      | 55  | 55      |
| b                                                   |               | 55  | 55      | 55  | 55      |
| c                                                   |               | 44  | 44      | 44  | 44      |
| d                                                   |               | 45  | 45      | 45  | 45      |
| e                                                   |               | 45  | 45      | 45  | 45      |
| f                                                   |               | 4.2 | 4.2     | 4.2 | 4.2     |
| g                                                   |               | 8   | 8       | 8   | 8       |
| g.1                                                 |               | 2   | 2       | 2   | 2       |
| h                                                   |               | 67  | 67      | 67  | 67      |
| k                                                   |               | 22  | 22      | 22  | 22      |
| l                                                   |               | 34  | 34      | 34  | 34      |
| Terminal for cond. cross<br>section (mm²) min.-max. |               | 4 4 | —10 —10 | 4 4 | —10 —10 |