

Data Sheet | Item Number: 260-337

4-conductor terminal block; without push-buttons; with fixing flange; 1-pole; for screw or similar mounting types; Fixing hole 3.2 mm Ø; 1.5 mm²; CAGE CLAMP®; green-yellow

<https://www.wago.com/260-337>



Color: ■ green-yellow

Ground terminal block, 260 Series, CAGE CLAMP®

This ground terminal block (item number 260-337) is designed for quick and easy connections. Our mini rail-mount terminal blocks are perfect for working in small spaces thanks to their compact design. With various mounting and actuation options, they offer complete flexibility. Rated current and voltage are key factors to consider when choosing a mini rail-mount terminal block, as they determine the product's suitability for different applications. This product has a rated voltage of 400 V and a rated current of 18 A. Strip lengths must be between 8 mm and 9 mm when connecting conductors to this ground terminal block. Featuring conductor terminals along with CAGE CLAMP®, this connector outperforms the competition. Our tried-and-tested universal connection known as CAGE CLAMP® is the industry standard for connection technology and electrical interconnections. Dimensions: 8 x 17 x 25.1 mm (width x height x depth). This ground terminal block is suitable for conductor cross sections ranging from 0.08 mm² to 1.5 mm². It has one level. The single potential can connect using the four clamping points. The green-yellow housing is made of polyamide (PA66) for insulation. An operating tool is used to operate this mini rail-mount terminal block. You can connect copper conductors thanks to side-entry wiring.

| Electrical data | | | |
|---|-------|--------------------------------|-------|
| Ratings per IEC/EN | | Ratings per UL | |
| Nominal voltage (III/3) | 400 V | Rated voltage UL (Use Group B) | 300 V |
| Rated impulse withstand voltage (III / 3) | 6 kV | Rated current UL (Use Group B) | 10 A |
| Rated current | 18 A | Rated voltage UL (Use Group C) | 300 V |
| | | Rated current UL (Use Group C) | 10 A |
| | | Rated voltage UL (Use Group D) | 600 V |
| | | Rated current UL (Use Group D) | 5 A |
| Ratings per CSA | | | |
| Rated voltage CSA (Use Group C) | 300 V | | |
| Rated current CSA (Use Group C) | 10 A | | |



| Connection data | | | |
|----------------------------|---|---------------------------------|-----------------------------------|
| Clamping units | 4 | Connection 1 | |
| Total number of potentials | 1 | | |
| Number of levels | 1 | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | Connection technology | CAGE CLAMP® |
| | | Actuation type | Operating tool |
| | | Connectable conductor materials | Copper |
| | | Solid conductor | 0.08 ... 1.5 mm² / 28 ... 16 AWG |
| | | Fine-stranded conductor | 0.08 ... 1.5 mm² / 28 ... 16 AWG |
| | | Strip length | 8 ... 9 mm / 0.31 ... 0.35 inches |
| | | Wiring direction | Side-entry wiring |

| Physical data | | |
|---------------|--|------------------------|
| Width | | 8 mm / 0.315 inches |
| Height | | 17.1 mm / 0.673 inches |
| Depth | | 25.1 mm / 0.988 inches |

| Mechanical data | | |
|-----------------|--|-----------------|
| Design | | horizontal type |
| Mounting type | | Mounting flange |
| Marking level | | Side marking |

| Material data | | |
|------------------------------------|--|--|
| Note (material data) | | Information on material specifications can be found here |
| Color | | green-yellow |
| Material group | | I |
| Insulation material (main housing) | | Polyamide (PA66) |
| Flammability class per UL94 | | V0 |
| Fire load | | 0.043 MJ |
| Weight | | 2.6 g |

| Environmental requirements | | |
|----------------------------------|--|-----------------|
| Processing temperature | | -35 ... +85 °C |
| Continuous operating temperature | | -60 ... +105 °C |

| Commercial data | | |
|-----------------------|--|---------------------------|
| Product Group | | 9 (Std Chassis Mt Blocks) |
| PU (SPU) | | 300 (50) pcs |
| Packaging type | | Box |
| Country of origin | | CH |
| GTIN | | 4044918592970 |
| Customs tariff number | | 85369010000 |



| Product classification | | |
|------------------------|--|----------------------|
| UNSPSC | | 39121409 |
| eCl@ss 10.0 | | 27-14-11-06 |
| eCl@ss 9.0 | | 27-14-11-06 |
| ETIM 9.0 | | EC001284 |
| ETIM 8.0 | | EC001284 |
| ECCN | | NO US CLASSIFICATION |

| Environmental Product Compliance | | |
|----------------------------------|--|------------------------|
| RoHS Compliance Status | | Compliant,No Exemption |

| Approvals / Certificates | | | | | | | | | | | |
|---|----------|---|----------|----------|------------------|---|---|---|---|---|---|
| General approvals | | Declarations of conformity and manufacturer's declarations | | | | | | | | | |
| | | | | | | | | | | | |
| Approval | Standard | Certificate Name | | | | | | | | | |
| CCA DEKRA Certification B.V. | EN 60998 | NTR-NL 6508 | | | | | | | | | |
| CCA DEKRA Certification B.V. | EN 60998 | 2110272.01 | | | | | | | | | |
| CSA DEKRA Certification B.V. | C22.2 | 70010891 | | | | | | | | | |
| UL Underwriters Laboratories Inc. | UL 1059 | E45172 | | | | | | | | | |
| | | <table><tr><th>Approval</th><th>Standard</th><th>Certificate Name</th></tr><tr><td>EU-Declaration of Confor- mity WAGO GmbH & Co. KG</td><td>-</td><td>-</td></tr><tr><td>UK-Declaration of Confor- mity WAGO GmbH & Co. KG</td><td>-</td><td>-</td></tr></table> | Approval | Standard | Certificate Name | EU-Declaration of Confor- mity WAGO GmbH & Co. KG | - | - | UK-Declaration of Confor- mity WAGO GmbH & Co. KG | - | - |
| Approval | Standard | Certificate Name | | | | | | | | | |
| EU-Declaration of Confor- mity WAGO GmbH & Co. KG | - | - | | | | | | | | | |
| UK-Declaration of Confor- mity WAGO GmbH & Co. KG | - | - | | | | | | | | | |

| Approvals for marine applications | | |
|---|-----------|------------------|
| | | |
| Approval | Standard | Certificate Name |
| ABS American Bureau of Ship- ping | - | 19-HG1869868-PDA |
| BV Bureau Veritas S.A. | EN 60947 | 07436/F0 BV |
| DNV GL Det Norske Veritas, Ger- manischer Lloyd | - | TAE00001V2 |
| LR Lloyds Register | IEC 60998 | LR22173030TA |



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 260-337

Download icon

| Documentation | | | |
|---------------|------------|-----------------|---------------|
| Bid Text | | | |
| 260-337 | 19.02.2019 | xml 3.23 KB | Download icon |
| 260-337 | 14.06.2017 | doc 24.50 KB | Download icon |

CAD/CAE-Data

CAD data

2D/3D Models 260-337

Download icon

CAE data

EPLAN Data Portal 260-337

Download icon

WSCAD Universe 260-337

Download icon

ZUKEN Portal 260-337

Download icon

1 Compatible Products

1.1 Required Accessories

1.1.1 End plate

1.1.1.1 End plate



[Item No.: 260-361](#)
End plate; with fixing flange; gray

1.2 Optional Accessories

1.2.1 Ferrule

1.2.1.1 Ferrule



[Item No.: 216-301](#)
Ferrule; Sleeve for 0.25 mm² / AWG 24; insulated; electro-tin plated; yellow



[Item No.: 216-131](#)
Ferrule; Sleeve for 0.25 mm² / AWG 24; uninsulated; electro-tin plated; silver-colored



[Item No.: 216-302](#)
Ferrule; Sleeve for 0.34 mm² / 22 AWG; insulated; electro-tin plated; light turquoise



[Item No.: 216-201](#)
Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; acc. to DIN 46228, Part 4/09.90; white



[Item No.: 216-101](#)
Ferrule; Sleeve for 0.5 mm² / AWG 22; uninsulated; electro-tin plated; silver-colored



[Item No.: 216-202](#)
Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; gray



[Item No.: 216-102](#)
Ferrule; Sleeve for 0.75 mm² / AWG 20; uninsulated; electro-tin plated; silver-colored



[Item No.: 216-203](#)
Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; red



1.2.1.1 Ferrule



Item No.: 216-103
Ferrule; Sleeve for 1 mm² / AWG 18; unin-
sulated; electro-tin plated



Item No.: 216-204
Ferrule; Sleeve for 1.5 mm² / AWG 16; in-
sulated; electro-tin plated; black



Item No.: 216-104
Ferrule; Sleeve for 1.5 mm² / AWG 16; un-
insulated; electro-tin plated; silver-colo-
red

1.2.2 Installation

1.2.2.1 Mounting accessories



Item No.: 209-137
Mounting adapter; can be used as end
stop; 6.5 mm wide; gray



Item No.: 209-123
Mounting foot with screw; can be screwed
on terminal blocks with fixing flange; 6.4
mm wide; gray

1.2.3 Jumper

1.2.3.1 Jumper



Item No.: 260-402
Jumper; for conductor entry; 2-way; insu-
lated; gray

1.2.4 Marking

1.2.4.1 Marking strip



Item No.: 210-833
Marking strips; 25 m on roll; 6 mm wide;
plain; Self-adhesive; white

1.2.5 Test and measurement

1.2.5.1 Testing accessories



Item No.: 260-405
Test plug module; with locking latches;
modular; for 4-conductor terminal blocks;
for 260 Series; gray



Item No.: 249-138
Test plug module; without locking device;
modular; for 4-conductor terminal blocks;
gray

1.2.6 Tool

1.2.6.1 Operating tool




Item No.: 210-658
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; angled; short; multicoloured

Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

Item No.: 210-657
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; short; multicoloured

Installation Notes


Installation



Assembling modular terminal blocks into terminal strips.


Mounting an end plate.

Conductor termination





CAGE CLAMP® connection
Inserting a conductor.
With ferruled conductors, it is necessary to use a terminal block one size larger than the conductor's nominal cross-section.

Commoning



Commoning with comb-style jumper bar.



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Distance between locking devices must be approximately 35 ... 40 mm!

Testing after the conductors have been terminated.



Marking



Marking with self-adhesive marking strips.

Marking by direct printing (upon request).