



Data Sheet | Item Number: 261-204

4-conductor terminal strip; without push-buttons; with fixing flanges; 4-pole; for screw or similar mounting types; Fixing hole 3.2 mm Ø; 2.5 mm²; CAGE CLAMP®; gray

<https://www.wago.com/261-204>



Color: ■ gray



Dimensions in mm

Through terminal block, 261 Series, operating tool

Connecting conductors is quick and easy with this through terminal block (item number 261-204). Our mini rail-mount terminal blocks are the perfect choice when space is limited. A large selection of mounting and actuation variants means you can find a suitable mini terminal block for every purpose. This also means you can adapt the terminal blocks to your unique requirements. Our mini rail-mount terminal block is rated for 500 V and is designed for use with a rated current of up to 24 A. Ensure that the strip lengths are between 8 mm and 9 mm when connecting conductors to this through terminal block. Featuring conductor terminals along with CAGE CLAMP®, this connector is highly versatile. Our reliable and maintenance-free CAGE CLAMP® connection makes it easy to connect all conductor types without having to prepare the conductor. For example, you don't need to crimp ferrules. This through terminal block is suitable for conductor cross sections ranging from 0.08 mm² to 2.5 mm². It features one level and sixteen clamping points for connecting four potentials / 4 poles. The gray housing is made of polyamide (PA66) for insulation. An operating tool is used to operate this mini rail-mount terminal block. The side-entry wiring allows you to connect copper conductors.

Electrical data

| Ratings per IEC/EN                        |                                                           |
|-------------------------------------------|-----------------------------------------------------------|
| Nominal voltage (III/3)                   | 500 V                                                     |
| Rated impulse withstand voltage (III / 3) | 6 kV                                                      |
| Rated current                             | 24 A                                                      |
| Legend (ratings)                          | (III / 3) Δ Overvoltage category III / Pollution degree 3 |

| Approvals per |       | UL 1059 |       |  |
|---------------|-------|---------|-------|--|
| Use group     | B     | C       | D     |  |
| Rated voltage | 300 V | 300 V   | 600 V |  |
| Rated current | 15 A  | 15 A    | 5 A   |  |

| Approvals per |   | CSA 22.2 No 158 |       |  |
|---------------|---|-----------------|-------|--|
| Use group     | B | C               | D     |  |
| Rated voltage | - | 300 V           | 600 V |  |
| Rated current | - | 10 A            | 5 A   |  |

Connection data

|                            |    |
|----------------------------|----|
| Clamping units             | 16 |
| Total number of potentials | 4  |
| Number of levels           | 1  |

| Connection 1                    |                                   |
|---------------------------------|-----------------------------------|
| Connection technology           | CAGE CLAMP®                       |
| Actuation type                  | Operating tool                    |
| Connectable conductor materials | Copper                            |
| Solid conductor                 | 0.08 ... 2.5 mm² / 28 ... 14 AWG  |
| Fine-stranded conductor         | 0.08 ... 2.5 mm² / 28 ... 14 AWG  |
| Strip length                    | 8 ... 9 mm / 0.31 ... 0.35 inches |
| Pole number                     | 4                                 |
| Wiring direction                | Side-entry wiring                 |



| Physical data |  |                        |
|---------------|--|------------------------|
| Width         |  | 54.1 mm / 2.13 inches  |
| Height        |  | 28.1 mm / 1.106 inches |
| Depth         |  | 18.1 mm / 0.713 inches |
| Module width  |  | 10 mm / 0.394 inches   |

| Mechanical data |  |                 |
|-----------------|--|-----------------|
| Design          |  | horizontal type |
| Mounting type   |  | Mounting flange |
| Marking level   |  | Side marking    |

| Material data                      |  |                                                                          |
|------------------------------------|--|--------------------------------------------------------------------------|
| Note (material data)               |  | <a href="#">Information on material specifications can be found here</a> |
| Color                              |  | gray                                                                     |
| Material group                     |  | I                                                                        |
| Insulation material (main housing) |  | Polyamide (PA66)                                                         |
| Flammability class per UL94        |  | V0                                                                       |
| Fire load                          |  | 0.269 MJ                                                                 |
| Halogen-free                       |  | Yes                                                                      |
| Weight                             |  | 16.6 g                                                                   |

| Environmental requirements       |  |                 |
|----------------------------------|--|-----------------|
| Processing temperature           |  | -35 ... +85 °C  |
| Continuous operating temperature |  | -60 ... +105 °C |

| Commercial data       |  |               |
|-----------------------|--|---------------|
| PU (SPU)              |  | 100 pcs       |
| Packaging type        |  | Box           |
| Country of origin     |  | DE            |
| GTIN                  |  | 4066966215076 |
| Customs tariff number |  | 85369010000   |

| Product classification |  |                      |
|------------------------|--|----------------------|
| UNSPSC                 |  | 39121410             |
| eCl@ss 10.0            |  | 27-14-11-06          |
| eCl@ss 9.0             |  | 27-14-11-06          |
| ETIM 9.0               |  | EC001284             |
| ETIM 8.0               |  | EC001284             |
| ECCN                   |  | NO US CLASSIFICATION |

| Environmental Product Compliance |  |                         |
|----------------------------------|--|-------------------------|
| RoHS Compliance Status           |  | Compliant, No Exemption |



Approvals / Certificates

General approvals



| Approval                             | Standard | Certificate Name |
|--------------------------------------|----------|------------------|
| CCA<br>DEKRA Certification B.V.      | EN 60998 | NTR-NL 6509      |
| CCA<br>DEKRA Certification B.V.      | EN 60998 | 2110272.02       |
| CSA<br>DEKRA Certification B.V.      | C22.2    | 70010891         |
| UR<br>Underwriters Laboratories Inc. | UL 1059  | E45172           |

Declarations of conformity and manufacturer's declarations

| Approval                                                | Standard | Certificate Name |
|---------------------------------------------------------|----------|------------------|
| EU-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                |
| UK-Declaration of Confor-<br>mity<br>WAGO GmbH & Co. KG | -        | -                |

Approvals for marine applications



| Approval                                | Standard  | Certificate Name |
|-----------------------------------------|-----------|------------------|
| ABS<br>American Bureau of Ship-<br>ping | -         | 19-HG1869868-PDA |
| BV<br>Bureau Veritas S.A.               | EN 60947  | 07436/F0 BV      |
| LR<br>Lloyds Register                   | IEC 60998 | LR22173030TA     |



Downloads

Environmental Product Compliance

| Compliance Search                           |
|---------------------------------------------|
| Environmental Product<br>Compliance 261-204 |



Documentation

| Bid Text |            |                 |                                                                                                     |
|----------|------------|-----------------|-----------------------------------------------------------------------------------------------------|
| 261-204  | 19.02.2019 | xml<br>3.11 KB  | <a href="#"></a> |
| 261-204  | 14.06.2017 | doc<br>25.00 KB | <a href="#"></a> |

















| CAD/CAE-Data                                                     |                                                                                                                                                                   |
|------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>CAD data</div> <div>2D/3D Models 261-204</div> <div>↓</div> | <div>CAE data</div> <div>EPLAN Data Portal 261-204</div> <div>↓</div> <div>WSCAD Universe 261-204</div> <div>↓</div> <div>ZUKEN Portal 261-204</div> <div>↓</div> |

1 Compatible Products

1.1 Optional Accessories



1.1.1 Ferrule

1.1.1.1 Ferrule

|                                                                                                                                                                                                                    |                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <div><b>Item No.: 216-301</b><br/>Ferrule; Sleeve for 0.25 mm² / AWG 24; insulated; electro-tin plated; yellow</div>             |  <div><b>Item No.: 216-302</b><br/>Ferrule; Sleeve for 0.34 mm² / 22 AWG; insulated; electro-tin plated; light turquoise</div>    |  <div><b>Item No.: 216-201</b><br/>Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; acc. to DIN 46228, Part 4/09.90; white</div> |  <div><b>Item No.: 216-101</b><br/>Ferrule; Sleeve for 0.5 mm² / AWG 22; un-insulated; electro-tin plated; silver-colored</div> |
|  <div><b>Item No.: 216-202</b><br/>Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; gray</div>              |  <div><b>Item No.: 216-102</b><br/>Ferrule; Sleeve for 0.75 mm² / AWG 20; un-insulated; electro-tin plated; silver-colored</div> |  <div><b>Item No.: 216-203</b><br/>Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; red</div>                                                          |  <div><b>Item No.: 216-103</b><br/>Ferrule; Sleeve for 1 mm² / AWG 18; un-insulated; electro-tin plated</div>                  |
|  <div><b>Item No.: 216-204</b><br/>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; black</div>             |  <div><b>Item No.: 216-104</b><br/>Ferrule; Sleeve for 1.5 mm² / AWG 16; un-insulated; electro-tin plated; silver-colored</div> |  <div><b>Item No.: 216-205</b><br/>Ferrule; Sleeve for 2.08 mm² / AWG 14; insulated; electro-tin plated; yellow</div>                                                   |  <div><b>Item No.: 216-206</b><br/>Ferrule; Sleeve for 2.5 mm² / AWG 14; insulated; electro-tin plated; blue</div>            |
|  <div><b>Item No.: 216-106</b><br/>Ferrule; Sleeve for 2.5 mm² / AWG 14; un-insulated; electro-tin plated; silver-colored</div> |                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                    |

1.1.2 Installation

1.1.2.1 Mounting accessories

|                                                                                                                                                                                          |                                                                                                                                                                                                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <div><b>Item No.: 209-137</b><br/>Mounting adapter; can be used as end stop; 6.5 mm wide; gray</div> |  <div><b>Item No.: 209-123</b><br/>Mounting foot with screw; can be screwed on terminal blocks with fixing flange; 6.4 mm wide; gray</div> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

1.1.3 Jumper

1.1.3.1 Jumper



**Item No.: 261-402**  
Jumper; for conductor entry; 2-way; insulated; gray

1.1.4 Marking

1.1.4.1 Marking strip



**Item No.: 210-833**  
Marking strips; 25 m on roll; 6 mm wide; plain; Self-adhesive; white

1.1.5 Test and measurement

1.1.5.1 Testing accessories



**Item No.: 261-405**  
Test plug module; with locking latches; modular; for 4-conductor terminal blocks; for 261 Series; gray



**Item No.: 249-139**  
Test plug module; without locking device; modular; for 4-conductor terminal blocks; gray

1.1.6 Tool

1.1.6.1 Operating tool



**Item No.: 210-658**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; angled; short; multicoloured




**Item No.: 210-720**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured



**Item No.: 210-657**  
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; short; multicoloured


Installation Notes

Conductor termination




**CAGE CLAMP® connection**  
Inserting a conductor.  
With ferruled conductors, it is necessary to use a terminal block one size larger than the conductor's nominal cross-section.

Commoning



Commoning with comb-style jumper bar.




Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Distance between locking devices must be approximately 35 ... 40 mm!




Testing after the conductors have been terminated.


Installation



Mounting and securing a terminal strip directly to the plate via screw-type flanges.



Terminal strip with mounting flanges  
Screwing a mounting foot (209-123).  
(Distance between mounting feet: approx. 25 ... 30 mm)



Terminal strip; with mounting flanges; for DIN-35 rail



Terminal strip with mounting flanges, for screw or similar mounting types, 3.2 mm mounting hole diameter (with 209-123 Mounting Foot also for DIN-35 rail)

Marking



Marking with self-adhesive marking strips.



Marking by direct printing (upon request).

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: [www.wago.com](https://www.wago.com)