



Color: ■ gray

Similar to illustration

Electrical data

Ratings per IEC/EN	
Rated current	24 A

Physical data

Width	25 mm / 0.984 inches
Height	4 mm / 0.157 inches
Depth	19.2 mm / 0.756 inches
Jumper assignment	1-2-3-4-5

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0.017 MJ
Weight	2.5 g

Commercial data

PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454083519
Customs tariff number	85366990990



Product classification		
UNSPSC		39121421

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 280-485	

Documentation				
Bid Text				
280-485	27.04.2017	doc 24.00 KB		
280-485	19.02.2019	xml 2.54 KB		

CAD/CAE-Data		
CAD data	CAE data	
2D/3D Models 280-485	EPLAN Data Portal 280-485	
	WSCAD Universe 280-485	
	ZUKEN Portal 280-485	


1 Compatible Products
1.1 Optional Accessories
1.1.1 Tool
1.1.1.1 Operating tool



[Item No.: 280-435](#)
Operating tool; made of insulating material; 5-way; gray

Installation Notes

Commoning



Commoning using comb-style jumper bars.
Push comb-style jumper bars down until fully inserted.

Commoning




4-conductor through terminal blocks, angled type, formation of groups with 3-way, comb-style jumper bars

Commoning



Carrier terminal blocks with component plugs, alternate comb-style jumper bars, 3-way comb-style jumper bar

Commoning



Commoning front-entry disconnect terminal blocks via comb-style jumper bar using a 10-pole operating tool