# Product datasheet Characteristics

## LX1FG024

TeSys F - contactor coil - LX1FG - 24 V AC 50 Hz



Range	TeSys	- 1
Product or component type	Contactor coil	5
Device short name	LX1FG	
Range compatibility	TeSys F LC1F contactor	
Product compatibility	LC1F225 LC1F185	July 6
Control circuit type	AC 50 Hz	
[Uc] control circuit voltage	24 V AC 50 Hz	
Average resistance	0.18 Ohm at 20 °C	
Inductance of closed circuit	0.03 H	
Operating time	2035 ms closing 715 ms opening	o c
Mechanical durability	10 Mcycles	<u></u>
Operating rate	<= 2400 cyc/h at <= 55 °C	

### Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.350.55 Uc at 55 °C drop-out 50/60 Hz 0.851.1 Uc at 55 °C operational 50/60 Hz	
Inrush power in VA	805 VA at 20 °C (cos f 0.3) 50 Hz	
Hold-in power consumption in VA	55 VA at 20 °C (cos f 0.3) 50 Hz	j.
Heat dissipation	1824 W at 50 Hz	

#### Environment

Ambient air temperature for operation	> -555 °C	— data
Product weight	0.55 kg	_ 5

#### Contractual warranty

Contractual warranty			
Warranty period	18 months		