Product datasheet Characteristics

LX1FK240

TeSys F - contactor coil - LX1FK - 240 V AC 40...400 Hz



Main

Main		
Range of product	TeSys F	
Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1FK	
Range compatibility	TeSys F LC1F contactor	
Control circuit type	AC 40400 Hz	
Control circuit voltage	240 V AC 40400 Hz	
Average resistance	1160 Ohm holding at 20 °C 44.5 Ohm inrush at 20 °C	
Inductance of closed circuit	5.75 H	
Product compatibility	LC1F500	
Operating time	100170 ms opening 4075 ms closing	
Mechanical durability	10 Mcycles	
Operating rate	2400 cyc/h at <= 55 °C	

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.30.5 Uc at 55 °C drop-out 40400 Hz 0.851.1 Uc at 55 °C operational 40400 Hz	
Inrush power in VA	1100 VA at 20 °C (cos f 0.9) 40400 Hz	
Hold-in power consumption in VA	18 VA at 20 °C (cos f 0.3) 40400 Hz	
Heat dissipation	18 W at 40400 Hz	

Environment

Ambient air temperature for operation	> -555 °C	_ <u>.</u>
/ into one can tomporation of operation		2
Product weight	1 15 kg	
1 Toddot Wolgin	1.15 kg	2

1

Warranty period

18 months

