# Product datasheet Characteristics

## LX1FF110

TeSys F - contactor coil - LX1FF - 110...115 V AC 50 Hz



#### Main

IVIAIII		
Range of product	TeSys F	
Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1FF	
Range compatibility	TeSys F LC1F contactor	
Control circuit type	AC 50 Hz	
Control circuit voltage	110115 V AC 50 Hz	
Average resistance	6.38 Ohm at 20 °C	
Inductance of closed circuit	0.86 H	
Product compatibility	LC1F150 LC1F115	
Operating time	515 ms opening 2335 ms closing	
Mechanical durability	10 Mcycles	
Operating rate	2400 cyc/h at <= 55 °C	

### Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.350.55 Uc at 55 °C drop-out 50/60 Hz 0.851.1 Uc at 55 °C operational 50/60 Hz	
Inrush power in VA	550 VA at 20 °C (cos f 0.3) 50 Hz	
Hold-in power consumption in VA	45 VA at 20 °C (cos f 0.3) 50 Hz	
Heat dissipation	1216 W at 50 Hz	

#### Environment

Ambient air temperature for operation	> -555 °C	<u>v</u>
- minimizer an temperature for operation	000	£
Product weight	0.43 kg	
i roddol worgin	0.70 Ng	å

Warranty period

18 months

