



Color: ■ yellow

Material data

Note (material data)		Information on material specifications can be found here
Color	yellow	
Material group	I	
Insulation material (main housing)	Polyamide (PA66)	
Flammability class per UL94	V0	
Fire load	0.013 MJ	
Weight	0.4 g	

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	100 (20) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332283212
Customs tariff number	39269097900

Product classification

UNSPSC	39121703
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
ECCN	NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search


Environmental Product Compliance 282-384

↓

Documentation				
Bid Text				
282-384	19.02.2019	xml	2.50 KB	↓
282-384	03.03.2017	doc	23.00 KB	↓

CAD/CAE-Data	
CAD data 2D/3D Models 282-384 ↓	CAE data WSCAD Universe 282-384 ↓ ZUKEN Portal 282-384 ↓

Installation Notes



Lock-out snaps into one of two notched positions, preventing accidental operation of the disconnect link.