

Locking cover; mechanically locks multiple links; 2-pole; transparent



Similar to illustration

| | |
|-------|------------------------|
| Width | 15.2 mm / 0.598 inches |
|-------|------------------------|

| | |
|-------|------------------------|
| Width | 15.2 mm / 0.598 inches |
|-------|------------------------|

Note (material data)

[Information on material specifications can be found here](#)

Note (material data)

[Information on material specifications can be found here](#)

| | |
|-------|-------------|
| Color | transparent |
|-------|-------------|

| Material group | IIIa |
|----------------|------|
|----------------|------|

| | |
|------------------------------------|--------------------|
| Insulation material (main housing) | Polycarbonate (PC) |
|------------------------------------|--------------------|

| | |
|-----------------------------|----|
| Flammability class per UL94 | V2 |
|-----------------------------|----|

| | |
|-----------|----------|
| Fire load | 0.065 MJ |
|-----------|----------|

| | |
|--------|-------|
| Weight | 1.1 g |
|--------|-------|

| | |
|----------------------------------|-----------------|
| Processing temperature | -35 ... +85 °C |
| Continuous operating temperature | -60 ... +105 °C |

| | |
|----------------------------------|-----------------|
| Processing temperature | -35 ... +85 °C |
| Continuous operating temperature | -60 ... +105 °C |

| | |
|-----------------------|----------------------------------|
| Product Group | 1 (Rail Mounted Terminal Blocks) |
| PU (SPU) | 50 (10) pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4017332283182 |
| Customs tariff number | 39269097900 |

| | |
|-----------------------|----------------------------------|
| Product Group | 1 (Rail Mounted Terminal Blocks) |
| PU (SPU) | 50 (10) pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4017332283182 |
| Customs tariff number | 39269097900 |



| Product classification | |
|------------------------|----------------------|
| UNSPSC | 39121421 |
| eCl@ss 10.0 | 27-14-11-92 |
| eCl@ss 9.0 | 27-14-11-92 |
| ETIM 9.0 | EC002848 |
| ETIM 8.0 | EC002848 |
| ECCN | NO US CLASSIFICATION |

| Environmental Product Compliance | |
|----------------------------------|------------------------|
| RoHS Compliance Status | Compliant,No Exemption |

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 282-882



↓

| Documentation | | | | |
|---------------|------------|-----|----------|---|
| Bid Text | | | | |
| 282-882 | 19.02.2019 | xml | 2.57 KB | ↓ |
| 282-882 | 03.03.2017 | doc | 23.50 KB | ↓ |

| CAD/CAE-Data | |
|----------------------|---------------------------|
| CAD data | CAE data |
| 2D/3D Models 282-882 | EPLAN Data Portal 282-882 |
| | WSCAD Universe 282-882 |
| | ZUKEN Portal 282-882 |

Installation Notes

Locking system



Snapping transparent locking cover onto 1–8 disconnect links:
a) Mechanically lock several links for multi-pole switching applications
b) Protect markers

Snapping transparent locking cover onto 1–8 disconnect links:
a) Mechanically lock several links for multi-pole switching applications
b) Protect markers

