



Color: ■ gray

Electrical data

Ratings per IEC/EN		Ex information	
Rated current	232 A	Rated current (Ex e II)	211 A

Physical data

Width	42 mm / 1.654 inches
Height	25 mm / 0.984 inches
Depth	47 mm / 1.85 inches
Jumper assignment	1-2

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0.162 MJ
Weight	55 g

Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918269490
Customs tariff number	85366990990



Product classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates					
General approvals			Approvals for hazardous areas		
					
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	154112	AEx Underwriters Laboratories Inc.	UL 60079	E185892 (AEx eb II C resp. Ex eb II C)


Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 285-495	

Documentation			
Bid Text			
285-495	19.02.2019	xml 2.62 KB	
285-495	04.01.2018	doc 22.50 KB	


CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 285-495	EPLAN Data Portal 285-495 
	WSCAD Universe 285-495 
	ZUKEN Portal 285-495 

Installation Notes

Commoning



Commoning with an adjacent jumper: insert the jumper above the conductor entry hole – prior to conductor termination. The nominal cross-section remains unchanged.



Removing jumper via operating tool.