



Color: light gray

Technical data		
Rated current		10 A

Connection data		
Solid conductor		0.08 ... 2.5 mm² / 28 ... 14 AWG
Fine-stranded conductor		0.08 ... 2.5 mm² / 28 ... 14 AWG
Strip length		9 ... 10 mm / 0.35 ... 0.39 inches

Physical data		
Width		12 mm / 0.472 inches
Depth		74.3 mm / 2.925 inches

Mechanical data		
Pluggable connector		pluggable

Material data		
Color		light gray
Fire load		0.204 MJ
Weight		11.2 g

Environmental requirements		
Ambient temperature (operation)		0 ... +55 °C
Ambient temperature (storage)		-25 ... +85 °C
Protection type		IP20



Commercial data	
Product Group	15 (I/O System)
PU (SPU)	25 (1) pcs
Packaging type	Box
Country of origin	CN
GTIN	4050821043928
Customs tariff number	85366990990

Product classification	
UNSPSC	39121402
eCl@ss 10.0	27-24-26-92
eCl@ss 9.0	27-24-26-92
ETIM 9.0	EC002584
ETIM 8.0	EC002584
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

General approvals			Approvals for marine applications		
			       		
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
UL	UL 1059	E45172	ABS	-	22-2219060
Underwriters Laboratories Inc.			American Bureau of Shipping		
			BSH	-	1104
			Bundesamt fuer Seeschifffahrt und Hydrographie		
			BV	-	13453/E0 BV
			Bureau Veritas S.A.		
			DNV	DNV-CG-0339, Aug. 2021	TAA0000194
			DNV GL SE		
			KR	-	KR HMB05880-AC001
			Korean Register of Shipping		
			LR	-	LR22180952TA
			Lloyds Register EMEA		
			PRS	-	TE/1101/880590/23
			Polski Rejestr Statków		
			RINA	-	ELE343521XG001
			RINA Germany GmbH		



Downloads			
Environmental Product Compliance			
Compliance Search			
Environmental Product Compliance 753-110			

Documentation			
Bid Text			
753-110	09.01.2019	docx 13.23 KB	
753-110	19.02.2019	xml 2.99 KB	

CAD/CAE-Data			
CAD data		CAE data	
2D/3D Models 753-110		EPLAN Data Portal 753-110	
		WSCAD Universe 753-110	
		ZUKEN Portal 753-110	