



Color: ■ gray

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	400 V
Rated impulse withstand voltage (III / 3)	6 kV
Rated current	24 A

Physical data

Width	14.5 mm / 0.571 inches
Height	6 mm / 0.236 inches
Jumper assignment	1-4

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.011 MJ
Weight	1.8 g

Commercial data

Product Group	17 (TOP JOB Installation Terminal Blocks)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918270922
Customs tariff number	85366990990



Product classification	
UNSPSC	39121410
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 780-454


↓

Documentation				
Bid Text				
780-454	19.02.2019	xml	2.91 KB	↓
780-454	28.04.2017	doc	24.00 KB	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 780-454	EPLAN Data Portal 780-454
	WSCAD Universe 780-454
	ZUKEN Portal 780-454

Installation Notes

Commoning



Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!

Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!

