




Features:

- Switched-mode power supply
- Natural convection cooling when horizontally mounted
- Encapsulated for use in control cabinets
- Suitable for both parallel and series operation
- Electrically isolated output voltage (SELV) per EN 60335-1 and UL 60950-1; PELV per EN 60204
- DIN-35 rail mountable in different positions
- Direct installation on mounting plate via cable grip

Technical data

Input		Output	
Phases	1	Nominal output voltage $U_{o\ nom}$	24 VDC (SELV)
Nominal input voltage $U_{i\ nom}$	1 x 100 ... 240 VAC	Output voltage range	22 ... 26 VDC (adjustable)
Input voltage range	1 x 90 ... 264 VAC; 125 ... 375 VDC	Default Setting	DC 24 V
Nominal mains frequency range	47 ... 63 Hz; 0 Hz	Nominal output current $I_{o\ nom}$	5 A (24 VDC; 110 ... 240 VAC); 4 A (24 VDC; 100 ... 240 VAC)
Input current I_i	$\leq 1\ A\ (230\ VAC); \leq 2\ A\ (115\ VAC)$	Nominal output power	120 W
Discharge current	$\leq 1.5\ mA$	Deviation	$\leq 1\ \%$
Inrush current	$\leq 18\ A$	Residual ripple	$\leq 200\ mV\ (peak\text{-}to\text{-}peak)$
Power factor correction (PFC)	Passive	Overload behavior	Constant power (in overload range: $1.05 \dots 1.4 \times I_{o\ nom}$); Shutdown and automatic restart in the event of a short circuit
Mains failure hold-up time	$\geq 10\ ms\ (230\ VAC)$		

Signaling and communication

Signaling	1 x LED DC OK (green)
Operation status indicator	Green LED (U_o)

Efficiency/power losses

Power loss P_l	$\leq 19\ W$
Efficiency (typ.)	88 % (230 VAC; 5 ADC)

Circuit protection

Internal fuse	F 2.5 A / 250 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	Circuit breaker: B6, B10



Safety and protection		
Isolation voltage (pri.-sec.)		DC 4.242 kV
Isolation voltage (pri.-PE)		DC 2.2 kV
Isolation voltage (sec.-PE)		0.7 kVDC
Protection class		I
Protection type		IP20; per EN 60529
Resistance to reverse feed		≤ 30 VDC
Overtoltage category		II
Pollution degree		2
Transient suppression (primary)		Varistor
Short-circuit-protected		Yes
Open-circuit-proof		Yes
Parallel operation		Yes
Series operation		Yes, for 2 devices of the same type
MTBF		> 300,000 h (per IEC 61709)

Connection data		
Note (conductor cross-section)	12 AWG: THHN, THWN	
		Connection 1
		Connection type 1
		Input/output
		Connection technology
		CAGE CLAMP®
		WAGO connector
		WAGO 236 Series
		Solid conductor
		0.08 ... 2.5 mm² / 28 ... 12 AWG
		Fine-stranded conductor
		0.08 ... 2.5 mm² / 28 ... 12 AWG
		Strip length
		6 ... 7 mm / 0.24 ... 0.28 inches

Physical data		
Width		60 mm / 2.362 inches
Height		130 mm / 5.112 inches
Depth from upper-edge of DIN-rail		99 mm / 3.898 inches

Mechanical data		
Mounting type		DIN-35 rail Screw mount

Material data		
Fire load		0.129 MJ
Weight		550 g

Environmental requirements		
Ambient temperature (operation)		-20 ... +60 °C
Ambient temperature (storage)		-25 ... +75 °C
Relative humidity		10 ... 95 % (no condensation permissible)
Derating		-3 %/K (> 45 °C)
Climatic category		3K3 (per EN 60721)



Standards and specifications	
Conformity marking	CE
Standards/specifications	EN 61204-3 EN 60335-1 EN 62368-1 UL 60950-1 UL 508 SEMI F47

Commercial data	
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4055143372442
Customs tariff number	85044083900

Product classification	
UNSPSC	39121004
eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 9.0	EC002540
ETIM 8.0	EC002540
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption
SCIP notification number (Bulgaria)	aa2613f5-6113-400e-be75-dc6756207f88
SCIP notification number (Czech Republic)	7ede9750-7374-4598-8c28-b0e5d82e38fc

Approvals / Certificates		
General approvals		Declarations of conformity and manufacturer's declarations
  		
Approval	Standard	Certificate Name
EAC GZO Almaty Standart	TP TC 004/2011	EAC CoC 03078
EAC GZO Almaty Standart	TP TC 020/2011	EAC CoC 03081
UL Underwriters Laboratories Inc.	UL 508	E255817
UR Underwriters Laboratories Inc.	UL 60950-1	E255815
Approval		Standard
EU-Declaration of Confor- mity WAGO GmbH & Co. KG		-
Approval		Certificate Name
MFD for SEMI F47 WAGO GmbH & Co. KG		-
Approval		Standard
UK-Declaration of Confor- mity WAGO GmbH & Co. KG		-



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-1722

Download icon

Documentation

Bid Text

787-1722

01.10.2019

xml

6.81 KB

Download icon

787-1722

01.10.2019

docx

20.59 KB

Download icon

ausschreiben.de 787-1722

Download icon

Instruction Leaflet

ECO Power Switched-Mode Power Supplies

V 1.5

21.12.2020

pdf

249.00 KB

Download icon

CAD/CAE-Data

CAD data

2D/3D Models 787-1722

Download icon

CAE data

EPLAN Data Portal 787-1722

Download icon

WSCAD Universe 787-1722

Download icon

ZUKEN Portal 787-1722

Download icon

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marking strip



Item No.: 210-831
Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white



Item No.: 210-832
Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

1.1.2 Tool

1.1.2.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured



Item No.: 210-769
SCREWDRIVER; green