




Color: ■ silver-colored

Physical data	
Width	1000 mm / 39.37 inches
Material data	
Color	silver-colored
Fire load	0 MJ
Weight	256 g
Commercial data	
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	IT
GTIN	4045454701109
Customs tariff number	72169180000
Product classification	
UNSPSC	39121702
eCl@ss 10.0	27-40-06-02
eCl@ss 9.0	27-40-06-02
ETIM 9.0	EC001285
ETIM 8.0	EC001285
ECCN	NO US CLASSIFICATION
Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption



Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance 790-145			↓

Documentation

Bid Text			
790-145	19.02.2019	xml 2.53 KB	↓
790-145	31.08.2017	doc 23.00 KB	↓

CAD/CAE-Data

CAD data	
2D/3D Models 790-145	↓

CAE data	
EPLAN Data Portal 790-145	↓
WSCAD Universe 790-145	↓
ZUKEN Portal 790-145	↓

1 Compatible Products

1.1 Optional Accessories


1.1.1 Shield termination

1.1.1.1 Shield termination



Item No.: [790-144](#)
Stand off; for carrier rail; suitable for M5 size screw; with special perforations

Installation Notes



Securing a spacer sleeve to a specialty slotted DIN-rail.



Securing an additional shield clamping saddle.



Tightening/removing a shield clamping saddle.



After connection, tighten the knurled screw to complete the installation.
Recommended tightening torque: 0.5 Nm



To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.