

# voltage release MX - 100..130 V DC/AC 50/60 Hz

47362

### Main

Range	MasterPacT	
Range of product	MasterPact NT MasterPact NW MasterPact NW DC	
Device short name	MX	
Product or component type	Voltage release	
Device application	Control	
Voltage release type	Opening coil Instantaneous voltage release	
Control type	Standard	
[Uc] control circuit voltage	100130 V AC 50/60 Hz 100130 V DC	
Circuit breaker mounting mode	Fixed	
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW Masterpact MasterPact NW DC	

### Complementary

Operating threshold	0.71.1 x Un opening
Response time	50 ms +/- 10 % for MasterPact NT 50 ms +/- 10 % for MasterPact NW
Supply holding power	4.5 VA

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.3 cm
Package 1 Length	8.1 cm
Package 1 Weight	1.162 kg

### **Contractual warranty**

Warranty 18 months

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	23
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Ad764790-535b-4a4e-825e-50fd804b5824
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

#### Use Again

○ Repack and remanufacture	
Recyclability potential, in %	74
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins