

(!) Discontinued

Auxiliary contact block, TeSys GV5 -GV6 - GV7, 1 C/O low level

Local distributor code: 395519057

GV7AB11

! Discontinued on: 15 Jul 2022

EAN Code: 3389110617481

Main

Range	TeSys	
Device short name	GV7AB	
Product or component type	Auxiliary contact block	
Device application	Signalling	
Range compatibility	TeSys TeSys GV5 motor circuit breaker TeSys TeSys GV6 motor circuit breaker TeSys TeSys GV7 motor circuit breaker	
Auxiliary contact composition	1 C/O	
Auxiliary contacts type	Low level contacts	
Auxiliary contacts operation	Instantaneous	
[Ith] conventional free air thermal current	6 A conforming to IEC 60947-5-1	
[Ue] rated operational voltage	<= 690 V AC 50/60 Hz <= 110 V DC	
[le] rated operational current	5 A AC-12 Ue: <= 690 V conforming to IEC 60947-5-1 5 A AC-15 Ue: <= 48 V conforming to IEC 60947-5-1 4 A AC-15 Ue: 110127 V conforming to IEC 60947-5-1 3 A AC-15 Ue: 230240 V conforming to IEC 60947-5-1 2.5 A AC-15 Ue: 380440 V conforming to IEC 60947-5-1 0.1 A AC-15 Ue: 660690 V conforming to IEC 60947-5-1 2 A DC-12 Ue: <= 48 V conforming to IEC 60947-5-1 0.5 A DC-12 Ue: 110 V conforming to IEC 60947-5-1 0.5 A DC-14 Ue: <= 24 V conforming to IEC 60947-5-1 0.25 A DC-14 Ue: 48 V conforming to IEC 60947-5-1 0.1 A DC-14 Ue: 110 V conforming to IEC 60947-5-1	
Minimum switching current	5 mA	
Minimum switching voltage	12 V	

Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60947-1	
Protection type	GG fuse 10 A maximum GB2CB circuit breaker 10 A maximum	
Mechanical durability	50000 cycles	
Mounting location	Inside the circuit breaker	
Connections - terminals	Screw clamps terminals 1 cable(s) 1.5 mm²flexible with cable end Screw clamps terminals 1 cable(s) 1.5 mm²flexible without cable end Screw clamps terminals 1 cable(s) 1.5 mm²rigid	
Net weight	0.015 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty 18 months

2 Nov 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Total lifecycle Carbon footprint	16
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant	

Use Again

○ Repack and remanufacture		
Recyclability potential, in %	56	
End of life manual availability	No need of specific recycling operations	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Connections and Schema

GV7 AE11, GV7 AB11

Add-on auxiliary contacts according to their location

Location 1 C/O contact

Location 2 Trip indication Location 3 Electrical fault indication Location 4 C/O contact