

# PC 153412



Sample image

**Order symbol :** PC 153412

**Product nr :** 7032710

**Description :** Enclosure, PC

**Remarks :** Grey cover

**EAN :** 6418074058454

**El. number :**

- Finland : 3435370
- Denmark : 8212004375
- Sweden : 2536142

**Including :** Base with screws for mounting plate/DIN-rail. cover with PUR gasket and stainless steel cover screws.

EURO153410-12

<b>Dimensions :</b>	<b>Height</b>	<b>Width</b>	<b>Depth</b>
mm :	150	340	120
inch :	5.91	13.39	4.72

#### **Materials :**

Material :	Polycarbonate
Base colour :	RAL_7035
Cover colour :	RAL 7035 -light grey
Gasket material :	Polyurethane

#### **Temperatures :**

Temperature °C (short term) :	-40 ... 120
Temperature °C (continuous) :	-40 ... 80
Temperature °F (short term) :	-40 ... 250
Temperature °F (continuous) :	-40 ... 175

#### **Accessories :**

TRH 34	DIN-35 Mounting rail, for enclosures: (307 x 35 x 7)
TRH 15	DIN-35 Mounting rail, for enclosures: (122 x 35 x 7)
TM 1534	Mounting plate, for enclosures: (303 x 136 x 1.5)
TH A	Grey plastic hinges (2 pcs) (30 x 20 x 12)

#### **Ratings :**

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK07; IK08;
electrical_insulation :	Totally insulated
Halogen free (DIN/VDE 0472, Part 815) :	Yes
UV resistance :	UL 746C
Flammability Rating :	UL 94 V0
Glow Wire Test (IEC 695-2-1) °C :	960C

#### **Certificates :**

SGSFimko\_EURONORD